

Price groups ("the old way")

Price groups offer a basic way of linking job fees to job types. The logic is quite simple:

- For relevant Job types and Units, you specify a fee
 - See screenshot below
- The fee is then automatically calculated based on, for example, the running time of the part

Editing record 1 Update record Cancel

[Dashboard](#) / [Tools & data](#) / [Price groups](#) / [Edit fees](#)

Template creation	2022-01-01	
Minutes	<input type="text" value="100"/>	SEK
Hours	<input type="text" value="Value"/>	SEK
Subtitles	<input type="text" value="Value"/>	SEK
Words	<input type="text" value="Value"/>	SEK
Subtitling	2022-01-01	
Minutes	<input type="text" value="80"/>	SEK
Hours	<input type="text" value="Value"/>	SEK
Subtitles	<input type="text" value="Value"/>	SEK
Words	<input type="text" value="Value"/>	SEK

How to use

- Create a Price group (under Tools & Data / Price groups)
 - This is the unchanging unit which you can connect to users
- Add at least one price list to the price group
 - By using price groups, you can update the fees over time and specify a point in time when the new fees are used.
 - The jobs, as a consequence, need a Delivery date in order for the fee to be calculated
- Attach Price groups to users/people
 - Here, as well, you can specify a date. These dates allow you to swap price groups for users over time without affecting the fees of old jobs.
- Specify that the jobs should use this form of calculation
 - This is done on the "Job fee" tab, under Price list calculation:
 - "Use project data" will combine project data such as the number of units for the part with a price group

- "Use specifications" will let you specify, for example, a different number of units, but still make use of a price group.
- Example: the running time of the part is 100 minutes, but the freelancer only translated half of it.

Limitations

- A price group only supports a single currency
- Exceptions cannot be made for different target languages
- Prices remain dynamic even after jobs are accepted or grabbed
- All of these issues are addressed by using a [Resource matrix](#) instead.

Revision #8

Created 2022-03-07 17:03:02 UTC by Plint

Updated 2022-06-01 14:58:52 UTC by Plint